

Portable dock boards

Professional and ergonomic

By means of the wheeled and lacquered steel (optionally galvanized) operating handle or lever frame, which is included in delivery, these large dock boards for flexible application are handled easily and can be positioned precisely by a single person. This dock board is the ideal solution in cases where there is no permanently installed loading/unloading aid, and flexibility must be ensured. Ergonomic handling is further enhanced by the unique, dual-hinged roll-on plate, which ensures smooth loading/unloading operations, because it adapts perfectly to the ramp and compensates unevennesses. In addition, the dock board is fitted with a rubber profile underneath, which prevents slipping and reduces noise. Optional, recessed forklift prong pockets for Types F 1515 to F 2020 permit fast transport to the loading/unloading site.



Type F 1520

Type	Load capacity kg	Length mm	Width mm	max. Height difference mm	Weight kg
F 1515	4.500	1.500	1.500	0 – 190	91
F 1517	4.700	1.500	1.750	0 – 190	104
F 1520	5.000	1.500	2.000	0 – 190	117
F 2015	4.000	2.000	1.500	0 – 250	115
F 2017	4.200	2.000	1.750	0 – 250	132
F 2020	4.500	2.000	2.000	0 – 250	149
F 2515	3.500	2.500	1.500	0 – 310	139
F 2517	3.700	2.500	1.750	0 – 310	160
F 2520	4.000	2.500	2.000	0 – 310	181
F 3015	3.000	3.000	1.500	0 – 370	163
F 3017	3.200	3.000	1.750	0 – 370	188
F 3020	3.500	3.000	2.000	0 – 370	213
F 3515	2.500	3.500	1.500	0 – 430	187
F 3517	2.700	3.500	1.750	0 – 430	216
F 3520	3.000	3.500	2.000	0 – 430	245

Available with side curbs **Type F 9019006** on request (for a surcharge)



Position it ...



... remove the operating handle...



... load/unload. Done!

Dock boards should not be used at angles of more than 12,5% (approx. 7°).